

## Power module - EMD-SL-PS- 24DC - 2885359

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Power modules, pluggable, for EMD-SL-..., supply voltage: 20 V DC ... 30 V DC

### Your advantages

- Separately adjustable startup and response delays
- Variable supply voltage range
- Adjustable via potentiometer on the front



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 049887
GTIN	4046356049887
Weight per Piece (excluding packing)	21.300 g
Custom tariff number	85043180
Country of origin	Austria

### Technical data

#### Dimensions

Width	32 mm
Height	35 mm
Depth	16 mm

#### Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C

# Power module - EMD-SL-PS- 24DC - 2885359

## Technical data

### Input data

Nominal input voltage	24 V DC
-----------------------	---------

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 5.0	27049002
eCl@ss 5.1	27049200
eCl@ss 6.0	27049000
eCl@ss 7.0	27049002
eCl@ss 8.0	27049002
eCl@ss 9.0	27040701

### ETIM

ETIM 4.0	EC002540
ETIM 5.0	EC002540
ETIM 6.0	EC002540

### UNSPSC

UNSPSC 6.01	30211916
UNSPSC 7.0901	39121535
UNSPSC 11	39121535
UNSPSC 12.01	39121535
UNSPSC 13.2	39121004

## Approvals

### Approvals

---

### Approvals

EAC

---


### Ex Approvals

---

## Power module - EMD-SL-PS- 24DC - 2885359

### Approvals

#### Approval details

EAC		RU *- DE.**08.B-02133
-----	-----------------------------------------------------------------------------------	--------------------------

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>