

VE Series

Features

- 3 ϕ ~ 18 ϕ , 85°C, 2,000 hours assured
- Chip type large capacitance capacitors
- Designed for surface mounting on high density PC board
- RoHS Compliance



Marking color: Black

Specifications

Items	Performance																																																																									
Category Temperature Range	-40°C ~ +85°C																																																																									
Capacitance Tolerance	±20% (at 120Hz, 20°C)																																																																									
Leakage Current (at 20°C)	<table><tr><td>Rated Voltage</td><td colspan="6">6.3 ~ 100V</td><td colspan="6">160 ~ 450V</td></tr><tr><td>Time</td><td colspan="6">after 2 minutes</td><td colspan="6">after 5 minutes</td></tr><tr><td>Case size</td><td colspan="3">3 ~ 10 φ</td><td colspan="3">12.5 ~ 18 φ</td><td colspan="3">12.5 ~ 18 φ</td><td colspan="3"></td></tr><tr><td>Leakage Current</td><td colspan="3">I = 0.01CV or 3μA, whichever is greater</td><td colspan="3">I = 0.03CV or 4μA, whichever is greater</td><td colspan="3">I = 0.04CV +100μA</td><td colspan="3"></td></tr></table> Where, C = rated capacitance in μF, V = rated DC working voltage in V												Rated Voltage	6.3 ~ 100V						160 ~ 450V						Time	after 2 minutes						after 5 minutes						Case size	3 ~ 10 φ			12.5 ~ 18 φ			12.5 ~ 18 φ						Leakage Current	I = 0.01CV or 3μA, whichever is greater			I = 0.03CV or 4μA, whichever is greater			I = 0.04CV +100μA															
Rated Voltage	6.3 ~ 100V						160 ~ 450V																																																																			
Time	after 2 minutes						after 5 minutes																																																																			
Case size	3 ~ 10 φ			12.5 ~ 18 φ			12.5 ~ 18 φ																																																																			
Leakage Current	I = 0.01CV or 3μA, whichever is greater			I = 0.03CV or 4μA, whichever is greater			I = 0.04CV +100μA																																																																			
Tanδ (at 120Hz, 20°C)	<table><tr><td>Rated Voltage</td><td>4</td><td>6.3</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td><td>63</td><td>100</td><td>160 ~ 250</td><td>400 ~ 450</td></tr><tr><td>3 ~ 10 φ</td><td>0.42</td><td>0.28</td><td>0.24</td><td>0.20</td><td>0.14</td><td>0.12</td><td>0.10</td><td>0.10</td><td>0.10</td><td>-</td><td>-</td></tr><tr><td>12.5 ~ 18 φ</td><td>-</td><td>0.38</td><td>0.34</td><td>0.30</td><td>0.26</td><td>0.22</td><td>0.18</td><td>0.14</td><td>0.10</td><td>0.20</td><td>0.25</td></tr></table> When the capacitance exceeds 1,000μF, 0.02 shall be added every 1,000μF increase.												Rated Voltage	4	6.3	10	16	25	35	50	63	100	160 ~ 250	400 ~ 450	3 ~ 10 φ	0.42	0.28	0.24	0.20	0.14	0.12	0.10	0.10	0.10	-	-	12.5 ~ 18 φ	-	0.38	0.34	0.30	0.26	0.22	0.18	0.14	0.10	0.20	0.25																										
Rated Voltage	4	6.3	10	16	25	35	50	63	100	160 ~ 250	400 ~ 450																																																															
3 ~ 10 φ	0.42	0.28	0.24	0.20	0.14	0.12	0.10	0.10	0.10	-	-																																																															
12.5 ~ 18 φ	-	0.38	0.34	0.30	0.26	0.22	0.18	0.14	0.10	0.20	0.25																																																															
Low Temperature Characteristics (at 120Hz)	Impedance ratio shall not exceed the values given in the table below. <table><tr><td colspan="2">Rated Voltage</td><td>4.0</td><td>6.3</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td><td>63</td><td>100</td><td>160 ~ 250</td><td>400 ~ 450</td></tr><tr><td rowspan="4">Impedance Ratio</td><td>Z(-25°C)</td><td>φ D < 12.5</td><td>7</td><td>4</td><td>4</td><td>3</td><td>2</td><td>2</td><td>2</td><td>2</td><td>-</td><td>-</td></tr><tr><td>/Z(+20°C)</td><td>φ D ≥ 12.5</td><td>-</td><td>5</td><td>5</td><td>4</td><td>2</td><td>2</td><td>2</td><td>2</td><td>3</td><td>6</td></tr><tr><td>Z(-40°C)</td><td>φ D < 12.5</td><td>15</td><td>8</td><td>5</td><td>4</td><td>3</td><td>3</td><td>3</td><td>3</td><td>-</td><td>-</td></tr><tr><td>/Z(+20°C)</td><td>φ D ≥ 12.5</td><td>-</td><td>14</td><td>12</td><td>10</td><td>5</td><td>4</td><td>3</td><td>3</td><td>6</td><td>10</td></tr></table>												Rated Voltage		4.0	6.3	10	16	25	35	50	63	100	160 ~ 250	400 ~ 450	Impedance Ratio	Z(-25°C)	φ D < 12.5	7	4	4	3	2	2	2	2	-	-	/Z(+20°C)	φ D ≥ 12.5	-	5	5	4	2	2	2	2	3	6	Z(-40°C)	φ D < 12.5	15	8	5	4	3	3	3	3	-	-	/Z(+20°C)	φ D ≥ 12.5	-	14	12	10	5	4	3	3	6	10
Rated Voltage		4.0	6.3	10	16	25	35	50	63	100	160 ~ 250	400 ~ 450																																																														
Impedance Ratio	Z(-25°C)	φ D < 12.5	7	4	4	3	2	2	2	2	-	-																																																														
	/Z(+20°C)	φ D ≥ 12.5	-	5	5	4	2	2	2	2	3	6																																																														
	Z(-40°C)	φ D < 12.5	15	8	5	4	3	3	3	3	-	-																																																														
	/Z(+20°C)	φ D ≥ 12.5	-	14	12	10	5	4	3	3	6	10																																																														
Endurance	<table><tr><td>Test Time</td><td>2,000 Hrs</td></tr><tr><td>Capacitance Change</td><td>Within ±20% of initial value (4V: ±30%)</td></tr><tr><td>Tanδ</td><td>Less than 200% of specified value (4V: < 300%)</td></tr><tr><td>Leakage Current</td><td>Within specified value</td></tr></table> * The above specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage applied for 2,000 hours at 85°C.												Test Time	2,000 Hrs	Capacitance Change	Within ±20% of initial value (4V: ±30%)	Tanδ	Less than 200% of specified value (4V: < 300%)	Leakage Current	Within specified value																																																						
Test Time	2,000 Hrs																																																																									
Capacitance Change	Within ±20% of initial value (4V: ±30%)																																																																									
Tanδ	Less than 200% of specified value (4V: < 300%)																																																																									
Leakage Current	Within specified value																																																																									
Shelf Life Test	Test time: 1,000 hours; other items are the same as those for the Endurance. The rated voltage shall be applied to the capacitors before the measurements for 160 ~ 450V (Refer to JIS C 5101-4 4.1).																																																																									
Ripple Current and Frequency Multipliers	<table><tr><td colspan="2">Freq. (Hz)</td><td>50</td><td>120</td><td>1k</td><td>10k up</td></tr><tr><td rowspan="2">Cap. (μF)</td><td>Under 1,000</td><td>0.80</td><td>1.00</td><td>1.25</td><td>1.40</td></tr><tr><td>1,000 < C ≤ 10,000</td><td>0.85</td><td>1.00</td><td>1.15</td><td>1.25</td></tr></table>												Freq. (Hz)		50	120	1k	10k up	Cap. (μF)	Under 1,000	0.80	1.00	1.25	1.40	1,000 < C ≤ 10,000	0.85	1.00	1.15	1.25																																													
Freq. (Hz)		50	120	1k	10k up																																																																					
Cap. (μF)	Under 1,000	0.80	1.00	1.25	1.40																																																																					
	1,000 < C ≤ 10,000	0.85	1.00	1.15	1.25																																																																					

Diagram of Dimensions

Fig. 1





Fig. 2



Lead Spacing and Diameter


Unit: mm

ϕD	L	A	B	C	W	P ± 0.2	Fig. No.
3	5.3 ± 0.2	3.3	3.3	4.1	0.45 ~ 0.75	0.8	1
4	5.3 ± 0.2	4.3	4.3	5.1	0.5 ~ 0.8	1.0	1
5	5.3 ± 0.2	5.3	5.3	5.9	0.5 ~ 0.8	1.5	1
6.3	5.3 ± 0.2	6.6	6.6	7.2	0.5 ~ 0.8	2.0	1
6.3	7.7 ± 0.3	6.6	6.6	7.2	0.5 ~ 0.8	2.0	1
8	6.5 ± 0.3	8.3	8.3	9.0	0.5 ~ 0.8	2.3	1
8	10 ± 0.5	8.3	8.3	9.0	0.7 ~ 1.1	3.1	1
10	7.7 ± 0.3	10.3	10.3	11.0	0.7 ~ 1.3	4.7	1
10	10 ± 0.5	10.3	10.3	11.0	0.7 ~ 1.3	4.7	1
12.5	13.5 ± 0.5	13.0	13.0	13.7	1.1 ~ 1.4	4.4	2
12.5	16 ± 0.5	13.0	13.0	13.7	1.1 ~ 1.4	4.4	2
16	16.5 ± 0.5	17.0	17.0	18.0	1.1 ~ 1.4	6.4	2
16	21.5 ± 0.5	17.0	17.0	18.0	1.1 ~ 1.4	6.4	2
18	16.5 ± 0.5	19.0	19.0	20.0	1.1 ~ 1.4	6.4	2
18	21.5 ± 0.5	19.0	19.0	20.0	1.1 ~ 1.4	6.4	2


(*): For 3 ~ 6.3 ϕ is 0.4 max.

Marking


$\phi D = 3 \text{ mm}$




$\phi D = 4 \sim 6.3 \text{ mm}$



$\phi D = 8 \sim 10 \text{ mm}$



$\phi D \geq 12.5 \text{ mm}$



Dimension: $\phi D \times L(\text{mm})$

Ripple Current: mA/rms at 120 Hz, 85°C

Dimension and Permissible Ripple Current

V. DC		4V (0G)		6.3V (0J)		10V (1A)		16V (1C)		25V (1E)		35V (1V)		50V (1H)		63 (1J)	
μF	Contents	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA
1	010													4×5.3	10	4×5.3	8
2.2	2R2													4×5.3	14	4×5.3	12
3.3	3R3									3×5.3	14	3×5.3	14	4×5.3	17	5×5.3	22
4.7	4R7					3×5.3	14	3×5.3	14	4×5.3	26	4×5.3	26	4×5.3	20	5×5.3	25
10	100			3×5.3	16	4×5.3	26	4×5.3	26	5×5.3	44	5×5.3	44	5×5.3	35	6.3×5.3 8×6.5	40 46
22	220	3×5.3	16	4×5.3	26	5×5.3	44	4×5.3 5×5.3	30 44	5×5.3 6.3×5.3	47 59	5×5.3 6.3×5.3	47 59	6.3×5.3 6.3×7.7	50 65	8×10	139
33	330	4×5.3	31	4×5.3	31	4×5.3 5×5.3	31 55	5×5.3	55	5×5.3 6.3×5.3	55 67	6.3×5.3 6.3×7.7	67 85	6.3×7.7 8×6.5	75 95	8×10	139
47	470	4×5.3	34	4×5.3 5×5.3	34 55	6.3×5.3	75	5×5.3 6.3×5.3	55 75	6.3×5.3 6.3×7.7	75 98	6.3×7.7 8×6.5	98 105	6.3×7.7 8×10	75 190	10×10	200
68	680	5×5.3	58	5×5.3 6.3×5.3	58 89	6.3×5.3	89	6.3×5.3	89	6.3×7.7	109	6.3×7.7	109	8×10	190	10×10	226
100	101	5×5.3 6.3×5.3	58 89	6.3×5.3	89	6.3×5.3 6.3×7.7	89 109	6.3×5.3 6.3×7.7 8×6.5	89 109 125	6.3×7.7 8×6.5	109 125	8×10	252	8×10	190	10×10	226
150	151											10×7.7	252				
220	221	6.3×5.3 6.3×7.7	89 124	6.3×5.3 6.3×7.7	89 124	6.3×7.7 8×6.5 8×10	124 175 270	6.3×7.7 8×10	124 270	8×10 10×7.7	270 270	8×10 10×10	270 370	10×10	320	12.5×13.5	500
330	331	6.3×7.7	124	6.3×7.7 8×6.5	124 190	8×10	290	8×10 10×7.7	290 290	10×10	400	10×10	400	12.5×13.5	600	12.5×16	600
470	471	8×10	290	8×10	290	10×7.7 10×10	290 400	10×10	400	10×10	400	12.5×13.5	680	12.5×16	740	16×16.5	850
680	681			10×7.7	290	10×10	410	10×10	410	12.5×13.5	680	12.5×13.5	680	16×16.5	1,000	18×16.5	1,100
1,000	102			10×10	430	10×10	430	12.5×13.5	750	12.5×13.5	750	16×16.5	1,100	18×16.5 16×21.5	1,350 1,400		
2,200	222			12.5×13.5	890	12.5×13.5	890	16×16.5	1,100	16×16.5	1,100	18×16.5 16×21.5	1,450 1,500				
3,300	332			12.5×16	1,000	16×16.5	1,300	16×16.5	1,300	18×16.5 16×21.5	1,450 1,500	18×21.5	1,750				
4,700	472			16×16.5	1,400	16×16.5	1,400	18×16.5 16×21.5	1,600 1,650	18×21.5	1,750						
6,800	682			18×16.5 16×21.5	1,700 1,750	18×16.5 16×21.5	1,700 1,750	18×21.5	2,000								
10,000	103			18×21.5	2,000	18×21.5	2,000										

V. DC		100V (2A)		160V (2C)		200V (2D)		250V (2E)		400V (2G)		450V (2W)	
μF	Contents	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA	$\phi D \times L$	mA
4.7	4R7									12.5×13.5	120	12.5×13.5	120
10	100	8×10	90					12.5×13.5	150	12.5×13.5	120	12.5×16	130
22	220	8×10	90			12.5×13.5	240	12.5×13.5	150	16×16.5	140	16×16.5	140
33	330	10×10	120	12.5×13.5	290	12.5×16	310	12.5×16	240	16×16.5	140	18×16.5	180
47	470	10×10	120	12.5×16	370	16×16.5	420	16×16.5	340	18×16.5	280	18×21.5	250
68	680	12.5×13.5	380	16×16.5	500	16×16.5	420	18×16.5 16×21.5	440 450	18×21.5	350		
100	101	12.5×13.5	440	18×16.5 16×21.5	650 690	18×16.5 16×21.5	550 590	18×21.5	490				
220	221	16×16.5	600										
330	331	18×16.5 16×21.5	780 850										

Part Numbering System

VE Series	470 μF	±20%	6.3V	Carrier Tape	8 ϕ ×10L	Pb-free and PET coating case
VE-	471	M	0J	TR	-	0810
Series Name	Capacitance	Capacitance Tolerance	Rated Voltage	Package Type	Terminal Type	Case size
						Lead Wire and Coating Type

Note: For more details, please refer to "Part Numbering System (SMD Type)" on page 15.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Lelon:](#)

[VE-101M1VTR-0810](#) [VE-101M1ETR-0806](#) [VE-470M1VTR-0806](#) [VE-100M1HTR-0605](#) [VE-471M1CTR-0810](#) [VE-331M0JTR-0806](#) [VE-220M2GTR-1616](#) [VE-4R7M1HTR-0505](#) [VE-330M1HTR-0806](#) [VE-221M1ATR-0806](#) [VE-101M1HTR-1010](#) [VE-470M1HTR-0810](#)