

Plugs for the world


Angled plug - Part no. 1411



- screw terminals
- with grommet
- especially suited for use with receptacles of the Cepex range

| Protection type | IP 44 | | | |
|---------------------------------------|------------------------|--|--|--|
| Ampere | 16 A | | | |
| Poles | Зр | | | |
| Voltage | 230 | | | |
| Hertz | 50-60Hz | | | |
| Earth position | 6h | | | |
| Contact | nickel plated contacts | | | |
| Connection technology Screw terminals | | | | |
| | | | | |

Std. Pack. 10 Qty.



| 2 MB 69 | Amp. | | 16 | | 32 | |
|------------------------------|----------|------|------|-----|-----|-----|
| 2 MB 45 | Poles | 3 | 4 | 3 | 4 | 5 |
| Dim. in mm | а | 107 | 129 | 96 | 96 | 101 |
| | ь | 53 | 58 | 72 | 72 | 72 |
| | h | - | _ | _ | _ | 115 |
| | i | 85 | 71 | 115 | 115 | — |
| | 0 | - | _ | - | _ | 70 |
| | р | 49 | 35 | 70 | 70 | _ |
| | У | 17,5 | 17,5 | 22 | 22 | 22 |
| | z | 7 | 7 | 11 | 11 | 11 |
| | α | 15° | _ | 8° | 8° | _ |
| Terminal for cor | d. cross | 1 | 1 | 2,5 | 2,5 | 2,5 |
| section (mm ²) m | inmax. | -2,5 | -2,5 | 6 | —6 | 6 |