

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2024.11.26	阿树

Specifications:
规格:
Voltage rating:125V AC/DC
额定电压: 125V AC/DC
Current rating:2A AC/DC
额定电流: 2A AC/DC
Contact Resistance:≤20MΩ
接触电阻: ≤20MΩ
Insulation Resistance:≥500MΩ
绝缘电阻:≥500MΩ
Dielectric strength:800V AC/minutenai
耐压: 800V AC/minute

PART NO.:

X1506 W R S-XX-9T SW
① ② ③ ④ ⑤ ⑥ ⑦

- ①Series No
②Category:W-Wafer
③Welding Board Angle:R-Stright 90°
④Welding Way:S-SMT
⑤Row No-Pin No:XX-02-16PIN
⑥Material:9T-PA9T 94V-0
⑦Plating Category:SW-Matte Tin Plating
(Tin:70u Min)

Poles	Dimensions(mm)		
	A	B	C
2	6.25	1.50	3.75
3	7.75	3.00	5.25
4	9.25	4.50	6.75
5	10.75	6.00	8.25
6	12.25	7.50	9.75
7	13.75	9.00	11.25
8	15.25	10.50	12.75
9	16.75	12.00	14.25
10	18.25	13.50	15.75
11	19.75	15.00	17.25
12	21.25	16.50	18.75
13	22.75	18.00	20.25
14	24.25	19.50	21.75
15	25.75	21.00	23.25
16	27.25	22.50	24.75

X1506WRS-XX-9TSW	PA9T UL 94V-0	Brass	Tin -Pated	X1506H
PART NO	Material	Material(pin)	Finish(Pin)	Suitable XKB Terminal

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERAUCES	



DESIGN	阿树	VIEW:	MODEL TYPE: 1.50mm Crimp Style Connectors
CHECKED		UNIT: mm/in	PART NO.: X1506WRS-XX-9TSW
APPROVED		SIZE: A4	DWG NO.:

SCALE	PAGE	REVISION
N/A	1/1	A1