



NOTE :
 - MARKING "A" is used to identify "STANDARD" terminal
 - CRIMPING SPECIFICATION ACCORDING TO AS-64322-001

MARK	DESIGNATION	MATERIAL
2	BOX TERMINAL	STAINLESS STEEL thickness=0.15 mm
1	BODY TERMINAL	high conductivity copper alloy thickness=0.2 mm

PART NUMBER	CONTACT AREA	CRIMPING AREA	UNDERLAYER	CRIMPING RANGE (mm2)	A±0.2	B±0.2	rC +0.15/-0.1	D±0.2	E±0.2	rF±0.1	WEIGHT (g)
0643221029	Sn	Sn	Ni	0.75	2.5	2.4	0.6	3.3	2.8	0.75	0.119
0643221219	Au 1.27μ MINI	Sn	Ni	0.50	2.3	2.2	0.6	3.1	2.6	0.75	0.117
0643221039	Sn	Sn	Ni	0.50	2.3	2.2	0.6	3.1	2.6	0.75	0.117
0643221239	Au 1.27μ MINI	Sn	Ni	0.22 to 0.44	2.0	1.7	0.6	3.1	2.6	0.75	0.112
0643221019	Sn	Sn	Ni	0.22 to 0.44	2.0	1.7	0.6	3.1	2.6	0.75	0.112
0643221229	Au 1.27μ MINI	Sn	Ni	0.22 to 0.44	2.0	1.7	0.6	3.1	2.6	0.75	0.112

(SKC) COTES CARACTERISTIQUES SPECIALES
 SPECIAL KEY CHARACTERISTICS
 ■ INDICATION DIMENSIONS S.P.C
 DENOTES S.P.C DIMENSIONS
 ● INDICATION DIMENSIONS CRITIQUES
 DENOTES CRITICAL DIMENSIONS
 ● INDICATION DIMENSIONS FONCTIONNELLES
 DENOTES FUNCTIONAL DIMENSIONS
 QUANTITE PAR FEUILLE INDIVIDUELLE
 QUANTITY PER INDIVIDUAL SHEET
 ■ 1 ● 0 ● 4 (SKC) 0

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

FUNCTIONAL SYMBOLS
 FA = 0
 FC = 0
 FP = 0

DIMENSION UNITS: mm
 SCALE: 20:1

GENERAL TOLERANCES (UNLESS SPECIFIED)
 ANGULAR TOL ± 2°
 4 PLACES ± 0.10000
 3 PLACES ± 0.1000
 2 PLACES ± 0.100
 1 PLACE ± 0.10
 0 PLACES ± 0.10

DIVISIONAL SYMBOLS

STATUS: Production
 DRWN: Nitin Venkatesh Shet
 CHK'D: Nitin Venkatesh Shet
 APPR: ChandrashekarS

2024-01-25 DOCUMENT NUMBER
 2024-01-30
 2024-01-30

CURRENT REV DESC: Dim 5 and Dim 10 tolerance update

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

FIRST ANGLE PROJECTION

DRAWING: A1-SIZE
 SERIES: 64322

MATERIAL NUMBER: SD-64322-001
 CUSTOMER: GENERAL MARKET
 SHEET NUMBER: 1 OF 1

PRODUCT SALES DRAWING
 CP RCPT TRM 0.6

DOCUMENT NUMBER: SD-64322-001
 DOC TYPE: PSD
 DOC PART: 000
 REVISION: E2

MOLEX