



AD230-9 TO

Description

Circular active area APD chip with NIR enhanced sensitivity. Metal can type hermetic TO52 package with clear glass window.

Features

- APD with 0.04 mm² active area
- Slow multiplication curve
- QE > 80% @ 750 nm-910 nm
- Fast rise time, low noise
- Optimum gain: 50-60

Applications


- Laser range finder
- High speed photometry
- High speed optical communications
- Medical equipment
- LIDAR

RoHS

2011/65/EU

2015/863/EU


[CLICK HERE >](#)
CONNECT WITH A SPECIALIST




Absolute maximum rating

| Symbol | Parameter | Min | Max | Unit |
|-------------------|-------------------------------|-----|------|------|
| T _{STG} | Storage temp | -55 | 125 | °C |
| T _{OP} | Operating temp | -40 | 100 | °C |
| M _{max} | Gain (I _{P0} = 1 nA) | 200 | | |
| I _{PEAK} | Peak DC current | | 0.25 | mA |

Spectral response (M = 100)



Schematic




Electro-optical characteristics @ 23°C


| Symbol | Characteristic | Test Condition | Min | Typ | Max | Unit |
|-----------------|-------------------------|--|--------------|------|------|-----------------|
| | Active area | | diameter 230 | | | μm |
| | Active area | | 0.04 | | | mm ² |
| I _D | Dark current | M = 100 | | 0.5 | 1 | nA |
| C | Capacitance | M = 100; f = 100 kHz | | 0.3 | | pF |
| | Responsivity | M = 100; λ = 905 nm | 52 | 58 | | A/W |
| t _R | Rise time | M = 100; λ = 905 nm; R _L = 50 Ω | | 0.5 | | ns |
| | Cut-off frequency | -3dB | | 0.6 | | GHz |
| V _{BR} | Breakdown voltage* | I _R = 2 μA | 160 | | 200 | V |
| | Temperature coefficient | Change of V _{BR} with temperature | 1.25 | 1.45 | 1.55 | V/K |
| | Excess noise factor | M = 100; calculated | | 2.5 | | |
| | Excess noise index | M = 100; calculated | | 0.2 | | |

* ±2V measuring tolerance on upper and lower limits


Quantum efficiency (23 °C)




Capacitance as fct of reverse bias (23 °C)



Multiplication as fct of bias (23 °C)




Dark current as fct of bias (23 °C)



Application hints:

- Please refer to document "Application note for APDs"
- For further questions please refer to document "Instructions for handling and processing"

Technical Drawing, Package: TO52



Package dimension

Small quantities: Foam pad, boxed (12 cm x 16.5 cm)

Disclaimer: Due to our strive for continuous improvement, specifications are subject to change within our PCN policy according to JESD46C.

AD230-9 TO

Optical inspection

Optical inspection according to failure catalogue for optical sensors FK INS 201.

Ordering Information

| Description | TE Part Number | MPQ |
|-------------------------------------|----------------|-----------|
| AD230-9 TO (TO52S1gw; Ubr 160-200V) | 3001345-F | 1,000 pcs |

CLICK HERE ›
CONNECT WITH A SPECIALIST

NORTH AMERICA
Tel +1 800 522 6752

EUROPE
Tel +31 73 624 6999

ASIA
Tel +86 0400 820 6015

te.com/sensors

TE Connectivity, TE, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2021 TE Connectivity Corporation. All Rights Reserved.

Version # 07/2022

