


REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2024.12.14	阿树





PART NO.:


X1270 W R-2xXX C-6T V01
① ② ③ ④ ⑤ ⑥ ⑦

- ①Series No
②Category:W-Wafer
③Welding Board Angle:R-Stright 90°
④Row No.-Pin No.:2xXX-2x03P~2x32P
⑤C:With Horns
⑥Material:6T-Nylon PA6T UL94V-0
⑦Planting Category:V01-All Gold Flash

Voltage rating:500V AC/DC
额定电压:500V AC/DC
Current rating:1.0A
额定电流:1.0A
Insulation resistance:1000MΩ Min
绝缘电阻:1000MΩ Min
Withstanding voltage:≥500V AC/minute
耐压:≥500VC/分钟
Temperature range:-40℃~+125℃
使用温度:-40℃~+125℃



Poles	DIMENSIONS	
	A	B
2x03	2.54	18.31
2x04	3.81	19.58
2x05	5.08	20.85
2x06	6.35	22.12
2x07	7.62	23.39
2x08	8.89	24.66
2x09	10.16	25.93
2x10	11.42	27.20
2x12	13.97	29.74
2x13	15.24	31.01
2x15	17.78	33.55
2x17	20.32	36.09
2x20	24.13	39.90
2x25	30.48	46.25
2x30	36.83	52.60
2x32	39.37	55.14



X1270WR-2xXXC-6TV01	Nylon-6T UL 94V-0	Brass	Gold Flash	X1270H-2xXX X1270H1-2xXX
PART NO	Material	Material(Pin And Solder Tabs)	Finish(Pin And Solder Tabs)	Suitable XKB Housing

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	



DESIGN	阿树	VIEW:	MODEL TYPE: 1.27mm BTB Style Connectors
CHECKED		UNIT: mm/in	PART NO.: X1270WR-2xXXC-6TV01
APPROVED		SIZE: A4	DWG NO.: