# **BGA Heat Sink - High Performance** maxiFLOW w/Thermal Tape





ATS Part#:

Description:

#### ATS-52350B-C1-R0

35.00 x 35.00 x 7.50 mm BGA Heat Sink - High Performance maxiFLOW w/Thermal Таре

Heat Sink Type: maxiFLOW Heat Sink Attachment: **Thermal Tape** Equivalent Part Number: ATS-52350B-C2-R0

\*Image above is for illustration purpose only.

#### Features & Benefits

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling .
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low .
- Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks •

### **Thermal Performance**

		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	5.3 °C/W	3.9 °C/W	3.2 °C/W	2.9 °C/W	2.6 °C/W	2.4 °C/W	2.2 °C/W
	Ducted Flow	3.4	N/A	N/A	N/A	N/A	N/A	N/A

### **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	35.00 mm	35.00 mm	7.50 mm	44.94 mm	T412	BLUE-ANODIZED
	<ul> <li>Dimension</li> <li>ATS-5235         <ul> <li>(Saint-Gol</li> <li>Thermal p application</li> <li>ATS reser performan</li> <li>ATS certifi</li> </ul> </li> </ul>	ves the right to upda	eight from the bottor act heat sink assemb e provided for referen ate or change its pro-	ly with an equivalen nce only. Actual perf ducts without notice -6 and REACH com	t thermal ormance to improv	interface material may vary by
*Image above is for illustration purpose only.						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Advanced Thermal Solutions: ATS-52350B-C1-R0