



|                        |               |                               |           |
|------------------------|---------------|-------------------------------|-----------|
| <b>EAN:</b>            | 4013288101389 | <b>Size:</b>                  | 50x7x6 mm |
| <b>Part number:</b>    | 05104617001   | <b>Weight:</b>                | 6 g       |
| <b>Article number:</b> | 848 HSS       | <b>Country of origin:</b>     | CN        |
|                        |               | <b>Customs tariff number:</b> | 82075060  |

- Twist bit for metal applications
- Hex shaft for very good power transfer
- HSS = high speed steel with split point
- Finely-tuned material elasticity for great durability
- Very good concentricity

High quality metal twist drill bits for precise drilling in metal. Made out of high speed steel (HSS). A finely-tuned material elasticity provides for a long service life. Very good concentricity. Tough viscous tempered bits ensure a particularly long service life. The hexagonal shaft ensures very good power transfer. Drive: 1/4" hexagon, suitable for holders as per DIN ISO 1173-D 6.3.

### Web link

[http://products.wera.de/en/bits\\_holders\\_adaptors\\_bit\\_sets\\_bit\\_sets\\_for\\_special\\_applications\\_848\\_hss.html](http://products.wera.de/en/bits_holders_adaptors_bit_sets_bit_sets_for_special_applications_848_hss.html)

Wera - 848 HSS  
05104617001 - 4013288101389

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

## Bit Sets for Special Applications

## Twist drill bits for metal applications



Twist drill bits – for metal applications • 1/4" drive suitable for holders as per DIN 3126-D 6.3 (ISO 1173) • Hexagon shaft for very high torque transfer • HSS = high speed steel with cone point • Finely adjusted material elasticity for long service life • Excellent concentricity • Tough-absorbing tempered bits for particularly long service life

## Further versions in this product family:

|                    | <br>mm | <br>mm | <br>mm |
|--------------------|-------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| 05104610001        | 3.0                                                                                       | 16.00                                                                                     | 38.0                                                                                        |
| 05104611001        | 3.1                                                                                       | 18.00                                                                                     | 40.0                                                                                        |
| 05104612001        | 3.3                                                                                       | 18.00                                                                                     | 40.0                                                                                        |
| 05104613001        | 4.0                                                                                       | 20.00                                                                                     | 44.0                                                                                        |
| 05104614001        | 4.1                                                                                       | 20.00                                                                                     | 44.0                                                                                        |
| 05104615001        | 4.2                                                                                       | 20.00                                                                                     | 45.0                                                                                        |
| 05104616001        | 5.0                                                                                       | 26.00                                                                                     | 50.0                                                                                        |
| <b>05104617001</b> | <b>5.1</b>                                                                                | <b>26.00</b>                                                                              | <b>50.0</b>                                                                                 |
| 05104618001        | 6.0                                                                                       | 26.00                                                                                     | 50.0                                                                                        |
| 05104619001        | 6.8                                                                                       | 30.00                                                                                     | 50.0                                                                                        |
| 05104620001        | 8.0                                                                                       | 32.00                                                                                     | 51.0                                                                                        |
| 05104621001        | 8.5                                                                                       | 33.00                                                                                     | 53.0                                                                                        |
| 05104622001        | 10.0                                                                                      | 38.00                                                                                     | 54.0                                                                                        |

## Web link

[http://products.wera.de/en/bits\\_holders\\_adaptors\\_bit\\_sets\\_bit\\_sets\\_for\\_special\\_applications\\_848\\_hss.html](http://products.wera.de/en/bits_holders_adaptors_bit_sets_bit_sets_for_special_applications_848_hss.html)

Wera - 848 HSS

05104617001 - 4013288101389

Wera Werkzeuge GmbH  
Korzerter Straße 21-25

D-42349 Wuppertal

Tel: +49 (0)2 02 / 40 45-0

E-Mail: [info@wera.de](mailto:info@wera.de)