

# UT 16 BK - Feed-through terminal block



3044197

<https://www.phoenixcontact.com/us/products/3044197>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 1000 V, nominal current: 76 A, number of connections: 2, connection method: Screw connection, Rated cross section: 16 mm<sup>2</sup>, cross section: 1.5 mm<sup>2</sup> - 25 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: black

## Your advantages

- The reducing bridges can be used to connect terminal blocks with different connection technologies, e.g., UT 35 screw terminal block with Push-in technology 2,5 Push-in terminal blocks, to form power blocks
- The flexible options for reducing bridging in the CLIPLINE complete system can be found in "Accessories for the CLIPLINE complete modular terminal block system"
- Easy and time-saving potential supply and distribution of large currents and cross sections up to 35 mm<sup>2</sup> with reducing bridges
- Tested for railway applications

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 3044197       |
| Packing unit                         | 50 pc         |
| Minimum order quantity               | 50 pc         |
| Sales key                            | BE01          |
| Product key                          | BE1111        |
| GTIN                                 | 4055626055275 |
| Weight per piece (including packing) | 30.583 g      |
| Weight per piece (excluding packing) | 30.583 g      |
| Customs tariff number                | 85369010      |
| Country of origin                    | TR            |

# UT 16 BK - Feed-through terminal block



3044197

<https://www.phoenixcontact.com/us/products/3044197>

## Technical data

### Product properties

|                       |                             |
|-----------------------|-----------------------------|
| Product type          | Feed-through terminal block |
| Area of application   | Railway industry            |
|                       | Machine building            |
|                       | Plant engineering           |
|                       | Process industry            |
| Number of connections | 2                           |
| Number of rows        | 1                           |
| Potentials            | 1                           |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 06 |
|------------------|----|

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 2.43 W |

### Connection data

|                                 |                    |
|---------------------------------|--------------------|
| Number of connections per level | 2                  |
| Nominal cross section           | 16 mm <sup>2</sup> |

### Level 1 above 1 below 1

|                                                                                           |                                             |
|-------------------------------------------------------------------------------------------|---------------------------------------------|
| Screw thread                                                                              | M5                                          |
| Tightening torque                                                                         | 2.5 ... 3 Nm                                |
| Stripping length                                                                          | 14 mm                                       |
| Internal cylindrical gage                                                                 | A7                                          |
| Connection in acc. with standard                                                          | IEC 60947-7-1                               |
| Conductor cross section rigid                                                             | 1.5 mm <sup>2</sup> ... 25 mm <sup>2</sup>  |
| Cross section AWG                                                                         | 14 ... 4 (converted acc. to IEC)            |
| Conductor cross section flexible                                                          | 1.5 mm <sup>2</sup> ... 25 mm <sup>2</sup>  |
| Conductor cross section, flexible [AWG]                                                   | 14 ... 4 (converted acc. to IEC)            |
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 1 mm <sup>2</sup> ... 16 mm <sup>2</sup>    |
| Flexible conductor cross section (ferrule with plastic sleeve)                            | 1 mm <sup>2</sup> ... 16 mm <sup>2</sup>    |
| 2 conductors with same cross section, solid                                               | 1 mm <sup>2</sup> ... 6 mm <sup>2</sup>     |
| 2 conductors with same cross section, flexible                                            | 1 mm <sup>2</sup> ... 6 mm <sup>2</sup>     |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve       | 1 mm <sup>2</sup> ... 6 mm <sup>2</sup>     |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.75 mm <sup>2</sup> ... 10 mm <sup>2</sup> |

# UT 16 BK - Feed-through terminal block



3044197

<https://www.phoenixcontact.com/us/products/3044197>

|                       |                                                                                                                              |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------|
| Nominal current       | 76 A                                                                                                                         |
| Maximum load current  | 101 A (with 25 mm <sup>2</sup> conductor cross section)                                                                      |
| Nominal voltage       | 1000 V                                                                                                                       |
| Note                  | Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area. |
| Nominal cross section | 16 mm <sup>2</sup>                                                                                                           |

## Ex data

### Rated data (ATEX/IECEx)

|                             |                                     |
|-----------------------------|-------------------------------------|
| Identification              | Ⓔ II 2 GD Ex eb IIC Gb              |
| Operating temperature range | -60 °C ... 110 °C                   |
| Ex-certified accessories    | 3047206 D-UT 16                     |
|                             | 1205066 SZS 1,0X4,0 VDE             |
|                             | 3022276 CLIPFIX 35-5                |
|                             | 3022218 CLIPFIX 35                  |
| List of bridges             | Plug-in bridge / FBS 2-12 / 3005950 |
| Bridge data                 | 73.5 A / 16 mm <sup>2</sup>         |
| Ex temperature increase     | 40 K (80.5 A / 16 mm <sup>2</sup> ) |
| Rated voltage               | 690 V                               |
| for bridging with bridge    | 690 V                               |
| Rated insulation voltage    | 630 V                               |
| output                      | (Permanent)                         |

### Ex level General

|                      |         |
|----------------------|---------|
| Rated current        | 73.5 A  |
| Maximum load current | 89.5 A  |
| Contact resistance   | 0.16 mΩ |

### Ex connection data General

|                                                       |                                            |
|-------------------------------------------------------|--------------------------------------------|
| Torque range                                          | 2.5 Nm ... 3 Nm                            |
| Nominal cross section                                 | 16 mm <sup>2</sup>                         |
| Rated cross section AWG                               | 6                                          |
| Connection capacity rigid                             | 1.5 mm <sup>2</sup> ... 25 mm <sup>2</sup> |
| Connection capacity AWG                               | 16 ... 4                                   |
| Connection capacity flexible                          | 1.5 mm <sup>2</sup> ... 16 mm <sup>2</sup> |
| Connection capacity AWG                               | 16 ... 6                                   |
| 2 conductors with same cross section, solid           | 1 mm <sup>2</sup> ... 6 mm <sup>2</sup>    |
| 2 conductors with the same cross-section AWG rigid    | 18 ... 10                                  |
| 2 conductors with same cross section, stranded        | 1 mm <sup>2</sup> ... 4 mm <sup>2</sup>    |
| 2 conductors with the same cross-section AWG flexible | 18 ... 12                                  |

## Dimensions

|                 |         |
|-----------------|---------|
| Width           | 12.2 mm |
| End cover width | 2.2 mm  |
| Height          | 55.5 mm |

# UT 16 BK - Feed-through terminal block



3044197

<https://www.phoenixcontact.com/us/products/3044197>

|                    |         |
|--------------------|---------|
| Depth              | 54.4 mm |
| Depth on NS 35/7,5 | 55 mm   |
| Depth on NS 35/15  | 62.5 mm |

## Material specifications

|                                                                         |                  |
|-------------------------------------------------------------------------|------------------|
| Color                                                                   | black (RAL 9005) |
| Flammability rating according to UL 94                                  | V0               |
| Insulating material group                                               | I                |
| Insulating material                                                     | PA               |
| Static insulating material application in cold                          | -60 °C           |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C           |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C           |
| Fire protection for rail vehicles (DIN EN 45545-2) R22                  | HL 1 - HL 3      |
| Fire protection for rail vehicles (DIN EN 45545-2) R23                  | HL 1 - HL 3      |
| Fire protection for rail vehicles (DIN EN 45545-2) R24                  | HL 1 - HL 3      |
| Fire protection for rail vehicles (DIN EN 45545-2) R26                  | HL 1 - HL 3      |
| Calorimetric heat release NFPA 130 (ASTM E 1354)                        | 28 MJ/kg         |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed           |
| Specific optical density of smoke NFPA 130 (ASTM E 662)                 | passed           |
| Smoke gas toxicity NFPA 130 (SMP 800C)                                  | passed           |

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 9.8 kV      |
| Result                | Test passed |

### Temperature-rise test

|                                                 |                                     |
|-------------------------------------------------|-------------------------------------|
| Requirement temperature-rise test               | Increase in temperature $\leq 45$ K |
| Result                                          | Test passed                         |
| Short-time withstand current 16 mm <sup>2</sup> | 1.92 kA                             |
| Result                                          | Test passed                         |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 2.2 kV      |
| Result                | Test passed |

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Mechanical tests

### Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

# UT 16 BK - Feed-through terminal block



3044197

<https://www.phoenixcontact.com/us/products/3044197>

## Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 32/NS 35 |
| Result                  | Test passed |

## Test for conductor damage and slackening

|                                |                              |
|--------------------------------|------------------------------|
| Rotation speed                 | 10 rpm                       |
| Revolutions                    | 135                          |
| Conductor cross section/weight | 1.5 mm <sup>2</sup> / 0.4 kg |
|                                | 16 mm <sup>2</sup> / 2.9 kg  |
|                                | 25 mm <sup>2</sup> / 4.5 kg  |
| Result                         | Test passed                  |

## Environmental and real-life conditions

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Oscillation/broadband noise

|                        |                                                |
|------------------------|------------------------------------------------|
| Specification          | DIN EN 50155 (VDE 0115-200):2018-05            |
| Spectrum               | Service life test category 2, bogie-mounted    |
| Frequency              | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level              | 6.12 (m/s <sup>2</sup> ) <sup>2</sup> /Hz      |
| Acceleration           | 3.12g                                          |
| Test duration per axis | 5 h                                            |
| Test directions        | X-, Y- and Z-axis                              |

### Shocks

|                                |                                   |
|--------------------------------|-----------------------------------|
| Pulse shape                    | Half-sine                         |
| Acceleration                   | 30g                               |
| Shock duration                 | 18 ms                             |
| Number of shocks per direction | 3                                 |
| Test directions                | X-, Y- and Z-axis (pos. and neg.) |

### Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, no longer than 24 h, -60 °C to +70 °C)                                                   |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                                                                              |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

# UT 16 BK - Feed-through terminal block



3044197

<https://www.phoenixcontact.com/us/products/3044197>

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## Drawings

Circuit diagram



# UT 16 BK - Feed-through terminal block



3044197

<https://www.phoenixcontact.com/us/products/3044197>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/3044197>

### DNV

Approval ID: TAE00001S9



### CSA

Approval ID: 13631

|             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Use group B |                       |                       |                   |                             |
|             | 600 V                 | 85 A                  | 16 - 4            | -                           |
| Use group C |                       |                       |                   |                             |
|             | 600 V                 | 85 A                  | 16 - 4            | -                           |



### IECEE CB Scheme

Approval ID: DE1-65779

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 1000 V                | 76 A                  | -                 | - 16                        |



### cULus Recognized

Approval ID: E60425

|                            | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|----------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Use group B                |                       |                       |                   |                             |
|                            | 600 V                 | 85 A                  | 16 - 4            | -                           |
| Multi-conductor connection | 600 V                 | 85 A                  | - 14              | -                           |
| Use group C                |                       |                       |                   |                             |
|                            | 600 V                 | 85 A                  | 16 - 4            | -                           |
| Multi-conductor connection | 600 V                 | 85 A                  | - 14              | -                           |



### LR

Approval ID: LR24100022TA



### VDE Zeichengenehmigung

Approval ID: 40020166

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 1000 V                | 76 A                  | -                 | 1.5 - 16                    |

# UT 16 BK - Feed-through terminal block



3044197

<https://www.phoenixcontact.com/us/products/3044197>



## ATEX

Approval ID: KEMA04ATEX2048U

|                          | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Only flexible conductors | 690 V                 | 73.5 A                | -                 | 1.5 - 16                    |
| Only rigid conductors    | 690 V                 | 89.5 A                | -                 | 1.5 - 25                    |



## cUL Recognized

Approval ID: E192998

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 600 V                 | 85 A                  | 16 - 4            | -                           |



## EAC Ex

Approval ID: RU C-DE.HA91.B.00066



## IECEx

Approval ID: IECEx KEM 06.0027U

|                          | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Only flexible conductors | 690 V                 | 73.5 A                | -                 | 1.5 - 16                    |
| Only rigid conductors    | 690 V                 | 89.5 A                | -                 | 1.5 - 25                    |



## UL Recognized

Approval ID: E192998

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 600 V                 | 85 A                  | 16 - 4            | -                           |



## CCC

Approval ID: 2020322313000622



## UKCA-EX

Approval ID: DEKRA 21UKEX0304U

cULus Recognized

# UT 16 BK - Feed-through terminal block



3044197

<https://www.phoenixcontact.com/us/products/3044197>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141120 |
| ECLASS-13.0 | 27250101 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# UT 16 BK - Feed-through terminal block



3044197

<https://www.phoenixcontact.com/us/products/3044197>

## Environmental product compliance

### EU RoHS

|                                         |                    |
|-----------------------------------------|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|-----------------------------------------|--------------------|

### China RoHS

|                                        |                                          |
|----------------------------------------|------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|                                        | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

# UT 16 BK - Feed-through terminal block



3044197

<https://www.phoenixcontact.com/us/products/3044197>

## Accessories

**i** Note: Applying some accessories below might limit this product.

### FBS 2-12 - Plug-in bridge

3005950

<https://www.phoenixcontact.com/us/products/3005950>



Plug-in bridge, pitch: 12 mm, number of positions: 2, color: red

**i** Max. current carrying capacity: 76 A

---

### RB 35-16 - Reducing bridge

3032169

<https://www.phoenixcontact.com/us/products/3032169>



Reducing bridge, pitch: 14 mm, number of positions: 2, color: red

**i** Max. current carrying capacity: 90 A

# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## RB 16-6 - Reducing bridge

3047072

<https://www.phoenixcontact.com/us/products/3047072>



Reducing bridge, pitch: 12.2 mm, number of positions: 2, color: red

 Max. current carrying capacity: 37 A

---

## RB UT 16-(2,5/4) - Reducing bridge

3047073

<https://www.phoenixcontact.com/us/products/3047073>



Reducing bridge, pitch: 11 mm, number of positions: 2, length: 31 mm, color: red

 Max. current carrying capacity: 40 A

# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## RB UT 16-ST(2,5/4) - Reducing bridge

3047099

<https://www.phoenixcontact.com/us/products/3047099>

Reducing bridge, pitch: 11 mm, number of positions: 2, length: 41 mm, color: red



 Max. current carrying capacity: 40 A

---

## AGK 4-UT 16 - Pick-off terminal block

3047125

<https://www.phoenixcontact.com/us/products/3047125>



Pick-off terminal block, nom. voltage: 1000 V, nominal current: 32 A, number of connections: 1, connection method: Screw connection, cross section: 0.14 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting type: on base element, color: gray

# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## D-UT 16 - End cover

3047206

<https://www.phoenixcontact.com/us/products/3047206>

End cover, depth: 47.3 mm, width: 2.2 mm, height: 52.8 mm, color: gray



---

## TPNS-UK - Partition plate

0706647

<https://www.phoenixcontact.com/us/products/0706647>

Partition plate, depth: 70 mm, width: 2 mm, height: 80 mm, color: gray



# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## WS UT 16 - Warning label

3047374

<https://www.phoenixcontact.com/us/products/3047374>

Warning sign for UT terminal blocks



---

## LPS-12/E - Service connector

3270600

<https://www.phoenixcontact.com/us/products/3270600>



Service connector, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: red

# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## LPS-12 - Service connector

3270601

<https://www.phoenixcontact.com/us/products/3270601>



Service connector, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: red

---

## LPO 16/E - Pick-off plug

3270531

<https://www.phoenixcontact.com/us/products/3270531>



Pick-off plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: gray

# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## LPO 16 - Pick-off plug

3270532

<https://www.phoenixcontact.com/us/products/3270532>



Pick-off plug, nom. voltage: 800 V, nominal current: 24 A, number of positions: 1, connection method: Push-in connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: gray

---

## NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/us/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/us/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/us/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/us/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

---

## NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/us/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/us/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/us/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/us/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

---

## NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/us/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/us/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/us/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/us/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

---

## NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/us/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/us/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

---

## NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/us/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/us/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/us/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

## UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/us/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



---

## NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/us/products/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

# UT 16 BK - Feed-through terminal block



3044197

<https://www.phoenixcontact.com/us/products/3044197>

## ZB 12:UNPRINTED - Zack marker strip

0812120

<https://www.phoenixcontact.com/us/products/0812120>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 12.2 mm, lettering field size: 12 x 10.5 mm, Number of individual labels: 5

---

## ZB 12 CUS - Zack marker strip

0824942

<https://www.phoenixcontact.com/us/products/0824942>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 12.2 mm, lettering field size: 10.5 x 12.15 mm, Number of individual labels: 5

## UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## ZB 12,LGS:L1-N,PE - Zack marker strip

0812146

<https://www.phoenixcontact.com/us/products/0812146>



Zack marker strip, Strip, white, labeled, printed horizontally: L1, L2, L3, N, PE, mounting type: latching, for terminal block width: 12.2 mm, lettering field size: 10.5 x 12.15 mm, Number of individual labels: 5

---

## UC-TM 12 - Marker for terminal blocks

0819194

<https://www.phoenixcontact.com/us/products/0819194>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: latching, for terminal block width: 12 mm, lettering field size: 11.45 x 10.5 mm, Number of individual labels: 40

## UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## UC-TM 12 CUS - Marker for terminal blocks

0824613

<https://www.phoenixcontact.com/us/products/0824613>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 12 mm, lettering field size: 11.45 x 10.5 mm, Number of individual labels: 40

---

## UCT-TM 12 - Marker for terminal blocks

0829144

<https://www.phoenixcontact.com/us/products/0829144>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: latching, for terminal block width: 12 mm, lettering field size: 10.8 x 9.6 mm, Number of individual labels: 30

# UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## UCT-TM 12 CUS - Marker for terminal blocks

0829630

<https://www.phoenixcontact.com/us/products/0829630>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 12 mm, lettering field size: 10.8 x 9.6 mm, Number of individual labels: 30

---

## X-PEN 0,35 - Marker pen

0811228

<https://www.phoenixcontact.com/us/products/0811228>



Marker pen without ink cartridge, for manual labeling of markers, labeling extremely wipe-proof, line thickness 0.35 mm

## UT 16 BK - Feed-through terminal block

3044197

<https://www.phoenixcontact.com/us/products/3044197>



## SZS 1,0X6,5 VDE - Screwdriver

1205079

<https://www.phoenixcontact.com/us/products/1205079>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 6.5 x 150 mm, 2-component grip, with non-slip grip

## PROJECT COMPLETE - Software

1050453

<https://www.phoenixcontact.com/us/products/1050453>



Intuitive planning and marking software for configuring terminal strips and for professional marking of marking materials for terminal blocks, conductors, cables, devices, and systems. The software is available for download

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)