



Part Number : 643221019

Product Description : 0.635mm CMC CP
Female Terminal, Tin Plated, for Square
0.6mm x 0.6mm Pins, Wire Size 0.22-0.44mm²

Series Number : 64322

Status : Active

Product Category : Crimp Terminals

Documents & Resources

Drawings

Drawing 643221019_sd.pdf

Packaging Design Drawing 313025040-000.pdf

Packaging Design Drawing 313025040-000.pdf

3D Models and Design Files

3D Model 643221019_stp.zip

Specifications

Application Specification AS-64318-002-001.pdf

Application Specification AS-64318-002-CH-001.pdf

Application Specification AS-64318-002-SP-001.pdf

Application Specification AS-64319-002-001.pdf

Application Specification AS-64319-002-CH-001.pdf

Application Specification AS-64319-002-FR-001.pdf

Application Specification AS-64319-002-SP-001.pdf

Application Specification AS-64322-001-001.pdf

Application Specification AS-64322-001-CH-001.pdf

Application Specification AS-98420-001-001.pdf

Application Specification AS-98420-001-CH-001.pdf

Application Specification AS-98420-002-001.pdf

Application Specification AS-98420-002-CH-001.pdf

Application Specification AS-98420-002-FR-001.pdf

Application Specification AS-98420-002-SP-001.pdf

Packaging Specification PK-98913-001-001.pdf

Product Specification PS-64319-002-001.pdf


Tooling Specifications

Crimp Specification CS-64322-001-001.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant with Exemption 44; 33
------------	---------------------------------

China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Crimp Terminals
Series	64322
Description	0.635mm CMC CP Female Terminal, Tin Plated, for Square 0.6mm x 0.6mm Pins, Wire Size 0.22-0.44mm ²
Application	Automotive, Signal, Wire-to-Board
Comments	Current tested on a 5 terminals loaded connector, current for temperature increase of 40°C; Current max = 6A for 0.635mm Terminal (0.75mm ² wire)
Product Family	CMC and CMX Sealed, Hybrid, Modular Connectors
Product Name	CMC,CP Terminal
UPC	883906129460

Electrical

Current - Maximum per Contact	6.0A
Voltage - Maximum	14V DC

Physical

Gender	Female
Material - Metal	Phosphor Bronze
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	0.160/g
Packaging Type	Reel
Plating min - Mating	2.000µm
Termination Interface Style	Crimp or Compression
Wire Insulation Diameter	1.15-1.40mm
Wire Size (AWG)	N/A
Wire Size mm ²	0.22-0.44

Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

Use with Part(s)

Description	Part Number
Power CMC Receptacles	<u>64318</u>
CMC Receptacles and Wire Caps	<u>64319</u>
CMC Receptacles and Wire Caps	<u>64320</u>
CMC Receptacles and Wire Caps	<u>64321</u>

Application Tooling

Global

Description	Part Number
PremiumGrade Hand Crimp Tool for CP 0.635mm Female Terminals for CMC Connector, 0.22-0.35mm ² Wire	<u>638119100</u>

Extraction Tool for 0.635mm CP Crimp Terminals for CMC Connector	<u>638132400</u>
--	------------------

This document was generated on Sep 15, 2024