

## Specification Sheet

Part Number: 596-00813



Solar Label, Printable, Spanish, PHOTOVOLTAIC DISCONNECT, 3.75" x 1.0", PET, Red, 50/roll

Article Number	596-00813
Type	ACDISCS
Color	Red (RD)
Features & Benefits	<ul style="list-style-type: none"><li>• Made with UV-stable inks and materials for durability and weather resistance.</li><li>• Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.</li><li>• High abrasion and scuff resistance for high-performance labeling.</li><li>• Meets NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.</li></ul>
Quantity Per	roll

**Product Description**

HellermannTyton pre-printed Solar Rating labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

**Short Description**

Solar Label, Printable, Spanish, PHOTOVOLTAIC DISCONNECT, 3.75" x 1.0", PET, Red, 50/roll

**Global Part Name**

ACDISCS-840/926-RD

**Technical Description**

Printable Solar Label, Spanish Version, PV AC DISCONNECT LABEL, 3.75" X 1.0", Red

**Local Order Number 2**

English Version: 596-00237

**Width W (Imperial)**

3.75

**Width W (Metric)**

92.25

**Thickness T (Metric)**

64.0

**Height H (Imperial)**

1.0

**Height H (Metric)**

25.4

**Material**

Type 840/926, Polyester (PET), UV stable, clear Polyester laminate

**Material Shortcut**

840/926

<b>Adhesive</b>	Acrylic
<b>Halogen free</b>	No
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature (Metric)</b>	-40°F to +302°F (-40°C to +150°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	CSA 66956
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	50
<b>Package Quantity (Metric)</b>	50
<b>Customs Number</b>	3919102055
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1
<b>Weight (Metric)</b>	0.521
<b>Weight (Imperial)</b>	1.14

