# LADR26

Time delay auxiliary contact block, TeSys Deca, 1NO + 1NC, off delay 1-30s, front, lugsring terminals



Main		=
Range	TeSys TeSys Deca	_
Product name	TeSys Deca	
Product or Component Type	Time delay auxiliary contact block	_
Range compatibility	TeSys D CAD[RETURN]TeSys D LC1D[RETURN]TeSys F LC1F[RETURN]TeSys F CR1F[RETURN]TeSys Deca CAD[RETURN]TeSys Deca LC1D	-
Mounting Location	Front	eof.
Pole contact composition	1 NO + 1 NC	r use ther
Contacts operation	Time delay	ion o
Timer type	Off delay	plicat
Time delay range	130 s	ic ap
[Ue] rated operational voltage	690 V AC 25400 Hz	n. ant specif
[le] rated operational current	6 A at 120 V AC-15 1.04 A at 690 V AC-15 0.55 A at 125 V DC-13 0.1 A at 600 V DC-13	; contained herein. ser applications. pect to the relevant specific application or use thereof, sined herein.
[Ui] rated insulation voltage	690 V IEC 60947-5-1 600 V UL 600 V CSA	the products for specific i acts with res
[Ith] conventional free air thermal current	10 A (at 140 °F (60 °C))	iance of the products in the products the products.
Standards	EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1 GB/T 14048.5 EN 50012 IEC 60335-1:Clause 30.2 IEC 60335-2-40:Annex JJ UL 60335-2-40:Annex JJ	s and/or tech advance to the performance of the products contained herein or determining suitability or reliability of these products for specific user applications. mplete risk spalysis, evaluation and testing of the products with respect to the relevancies shall be exponsible or liable for misuse of the information contained herein.
Product Certifications	CB[RETURN]UL[RETURN]CSA[RETURN]CCC[RETURN]	- 10 10 10 10 10 10 10 10 10 10 10 10 10
		s and/or tech for determint omplete risk ries shall be
140 A AC 250 A DC		jeneral description I is not to be used appropriate and α
100 A 140 °F (60 °C) 1 s 120 A 140 °F (60 °C) 500 140 A 140 °F (60 °C) 100		The information provided in this documentation contains general description. This documentation is not intended as a substitute for and is not to be used it is the duty of any such user or integrator to perform the appropriate and or Neither Schneider Electric Industries SAS nor any of its affiliates or subsidia
GG fuse 10 A		on contains guitute for and perform the rany of its at
5 Mcycles		ation of bstitu to per nor ar
5 mA		ments s a su rator SAS r
17 V		docur led as integ tries \$
	no overlap between NC and NO contact overlap between NC and NO contact	ovided in this documentation is not intended as a substance in such user or integrator to Electric Industries SAS nor
> 10 MOhm		ovide n is r / such Elect
Lugs-ring terminals 0.3 in	(8 mm))	The information provided in this documentaric This documentation is not intended as a substit is the duty of any such user or integrator to Neither Schneider Electric Industries SAS no
		The infor This doci It is the c
Is On Schneider	1	

_				
Co	mn	lem	ent	tarv

140 A AC	
250 A DC	
100 A 140 °F (60 °C) 1 s	
120 A 140 °F (60 °C) 500 ms 140 A 140 °F (60 °C) 100 ms	
GG fuse 10 A	
5 Mcycles	
5 mA	
17 V	
1.5 Ms on de-energisation no overlap between NC and NO contact	
1.5 ms on energisation no overlap between NC and NO contact	
> 10 MOhm	
Lugs-ring terminals 0.3 in (8 mm))	

Tightening torque	15.05 Lbf.ln (1.7 N.m) flat Ø 6 mm	
	15.05 Lbf.In (1.7 N.m) Philips No 2	
	15.05 lbf.in (1.7 N.m) pozidriv No 2	
Height	1.9 in (48 mm)	
Width	1.7 in (44 mm)	
Depth	2.4 in (61 mm)	
Color	Dark grey	

### Environment

Environmental characteristic	Normal environment
IP degree of protection	IP2X conforming to IEC 60529
Protective treatment	TH IEC 60068
Ambient Air Temperature for Storage	-76176 °F (-6080 °C)
Ambient air temperature for operation	-40158 °F (-4070 °C)
Operating altitude	9842.52 ft (3000 m)

# Ordering and shipping details

Category	US10I1222341
Discount Schedule	0112
GTIN	3389110821864
Returnability	No
Country of origin	FR

# Packing Units

Unit Time of Declares 4	DOE
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.6 in (6.5 cm)
Package 1 Width	2.0 in (5 cm)
Package 1 Length	2.0 in (5 cm)
Package 1 Weight	2.6 oz (75 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	2.05 in (5.2 cm)
Package 2 Width	5.1 in (13 cm)
Package 2 Length	9.4 in (24 cm)
Package 2 Weight	26.8 oz (760 g)
Unit Type of Package 3	S03
Number of Units in Package 3	140
Package 3 Height	11.8 in (30 cm)
Package 3 Width	11.8 in (30 cm)
Package 3 Length	15.7 in (40 cm)
Package 3 Weight	24.593 lb(US) (11.155 kg)

### Offer Sustainability

Green Premium product	
WARNING: Cancer - www.P65Warnings.ca.gov	
☑ REACh Declaration	
Compliant with Exemptions	
Yes	
Yes	
₽¥Yes	
China RoHS Declaration	
Product Environmental Profile	
	WARNING: Cancer - www.P65Warnings.ca.gov  REACh Declaration  Compliant with Exemptions  Yes  Yes  Yes  China RoHS Declaration

Circularity Profile	No need of specific recycling operations	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	
Contractual warranty		
Warranty	18 months	