



RECOMMEND P.C.B. LAYOUT

NOTES:

- 1.材料规格 MATERIAL SPECIFICATION:
  - 1) 胶壳 HOUSING MATERIAL:BLACK LCP ROHS;
  - 2) 外壳 SHELL MATERIAL:SPCC T=0.30  
电镀 PLATING:NICKE;
  - 3) 端子 TERMINAL: C5191 T=0.25  
电镀 PLATING:SEMI GOLD TIN G/F;
- 2.电气特性 ELECTRICAL CHARACTERISTIC:
  - 1) 绝缘电阻 INSULATION RESISTANCE: 1000MΩ MIN;
  - 2) 接触电阻 CONTACT RESISTANCE: 30mΩ MAX;
  - 3) 耐压 WITHSTANDING VOLTAGE: 500V AC;
- 3.机器特性 MECHANICAL CHARACTERISTICS:
  - 1) 插入力 INSERTION FORCE:3.57Kgf Max;
  - 2) 拔出力 EXTRACTION FORCE:1.02Kgf Min;

						ANGLAR	±5°	
ΔX						L ≤ 4	±0.2	
ΔX						4 < L ≤ 16	±0.3	
ΔX						16 < L ≤ 63	±0.4	
MARK						L > 63	±0.5	
REVISIONS							UNSPECIFIED TOLERANCES	
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn								

DSND		DATE		SCALE: N/A	MODEL TYPE: USB 2.0	
DWN		DATE		VIEW:	PART NO.:	
CHKD		DATE		UNIT: mm/in	DWG NO.:	
APPD		DATE		SIZE: A4	U221-04XN-4BVS70-S1	
XKB INDUSTRIAL PRECISION CO.,LIMITED				WEIGHT	SHEET	REVISION
				1.0g	1/1	A0