

COAXIAL CONNECTOR, PC 1.85, 50 Ohm, Straight PCB jack (female)

82_PC185-S50-0-201/199_N

Properties

- For stripline configurations
- Fast and easy installation
- Precision testing up to 67 GHz
- Reusable design
- Mechanical intermateable with PC 2.4 (2.4 mm standard)



Product configuration		
Interface type	Gender	Standard
PC 1.85	jack	IEEE STD 287
Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Stainless Steel	Passivated (Plating)
Insulator	PEI (Polyether-imide)	
Electrical data		
Impedance	50 Ω	
Interface frequency	67 GHz	
Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 67 GHz	17 dB	1.33
Mechanical data		
Weight	0.0024 kg	
Mating cycles	500	
Environmental data		
Operation temperature	-40 °C ... 165 °C	

COAXIAL CONNECTOR, PC 1.85, 50 Ohm, Straight PCB jack (female)

82_PC185-S50-0-201/199_N

Ordering Information Table

Item number	Item description
85221626	82_PC185-S50-0-201/199_NE

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P41026 / Date of publication: 23.05.2024 / uncontrolled copy