

isc Silicon NPN Power Transistor
KTC3503
DESCRIPTION



- Low Collector Saturation Voltage
- High breakdown voltage
- Silicon NPN epitaxial planar transistor
- Small reverse transfer capacitance and excellent high frequency characteristic
- Complement to KTA1381
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- For high definition CRT display ,video output

ABSOLUTE MAXIMUM RATINGS(T_a=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V _{CBO}	Collector-Base Voltage	300	V
V _{CEO}	Collector-Emitter Voltage	300	V
V _{EBO}	Emitter-Base Voltage	5	V
I _c	Collector Current-Continuous	0.1	A
P _c	Collector Power Dissipation @ T _c =25°C	7	W
T _J	Junction Temperature	150	°C
T _{stg}	Storage Temperature Range	-55~150	°C



isc Silicon NPN Power Transistor

KTC3503

ELECTRICAL CHARACTERISTICS

T_c=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CBO}	Collector-Base breakdown voltage	I _C =10μA ; I _B =0	300			V
V _{(BR)CEO}	Collector-emitter breakdown voltage	I _C =1mA ; I _B =0	300			V
V _{(BR)EBO}	Emitter-base breakdown voltage	I _E =10μA ; I _C =0	5			V
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C =20mA ; I _B = 2mA			0.6	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _C =20mA ; I _B = 2mA			1.0	V
I _{CBO}	Collector Cutoff Current	V _{CB} = 300V ; I _E = 0			1.0	μ A
I _{EBO}	Emitter Cutoff Current	V _{EB} = 4V ; I _C = 0			1.0	μ A
h _{FE}	DC Current Gain	I _C = 10mA ; V _{CE} = 10V	60		200	
f _T	Current-Gain—Bandwidth Product	I _E = -10mA ; V _{CE} = 10V		150		MHz

◆ h_{FE} Classifications

O	Y
60-120	100-200

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.