

# isc Adjustable Voltage Regulator


# LM317

## FEATURES

- Output Voltage Range :1.2V to 37V
- Output Current In Excess of 1.5A
- 0.1% Line and Load Regulation
- Floating Operation for High Voltage
- 100% tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

## DESCRIPTION

- They are designed to supply more than 1.5A of load current with an output voltage adjustable over a 1.2 to 37V range.
- The nominal output voltage is selected by means of only a resistive divider, making the device exceptionally easy to use and eliminating the stocking of many fixed regulators.




## ABSOLUTE MAXIMUM RATING (T<sub>a</sub>=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V <sub>i</sub> - V <sub>o</sub>	Input-output Differential Voltage	40	V
I <sub>o</sub>	Output Current	1.5	A
P <sub>D</sub>	Power Dissipation	Internally Limited	W
T <sub>OP</sub>	Operating Junction Temperature	0~125	°C
T <sub>STG</sub>	Storage Temperature	-65~125	°C

## THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R <sub>th j-c</sub>	Thermal Resistance, Junction to Case	5	°C/W
R <sub>th j-a</sub>	Thermal Resistance, Junction to Ambient	35	°C/W



**isc Adjustable Voltage Regulator**
**LM317**
**• ELECTRICAL CHARACTERISTICS**

 ( $V_i - V_o = 5V$ ,  $I_o = 0.5A$ ,  $I_{MAX} = 1.5A$ ,  $P_{MAX} = 20W$ , unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$\Delta V_o$	Line Regulation	$V_i - V_o = 3V$ to $40V$ ; $I_o = 10mA$ to $1.5A$			0.07	%/V
$S_{VR}$	Ripple Rejection	$V_o = 10V$ ; $f = 120Hz$ ; $C_{ADJ} = 10 \mu F$	66			dB
$\Delta V_o$	Load Regulation	$I_o = 10mA$ to $1.5A$ ; $V_o \leq 5V$ ; $T_j = 25^\circ C$			25	mV
		$I_o = 10mA$ to $1.5A$ ; $V_o > 5V$ ; $T_j = 25^\circ C$			0.5	%
$I_o$ (min)	Minimum Load Current	$V_i - V_o = 40V$			12	mA
$I_o$ (max)	Maximum Load Current	$V_i - V_o \leq 15V$	1.5			A
		$V_i - V_o = 40V$ ; $T_j = 25^\circ C$		0.3		A
$I_{ADJ}$	Adjustment Pin Current	$V_i - V_o = 5V$ ; $I_o = 500mA$			100	$\mu A$
$\Delta I_{ADJ}$	Adjustment Pin Current	$V_i - V_o = 3V$ to $40V$ ; $I_o = 10mA$ to $1.5A$			5	$\mu A$
$V_{REF}$	Reference Voltage	$V_i - V_o = 3V$ to $40V$ ; $I_o = 10mA$ to $1.5A$ , $P \leq 15W$	1.2	1.25	1.3	V

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.