



■ Specifications.

- Voltage rating: 250V AC/DC
- Current rating: 5A AC/DC
- Withstanding voltage: 1500V AC/minute
- Temperature range: -25 °C ~ +85 °C
- Insulation resistance: 1000mΩ Min
- Contact resistance: 20mΩ Max
- Material: Phosphor bronze Tin-plated
- Applicable Wire Sizes: AWG#18~22

X5080 T -P SN
① ② ③ ④

- ① Series No.
- ② Category : T-Terminal
- ③ Material: P-Phosphor bronze
- ④ Plating style: SN-Bright Tin plating

X5080T-PSN	Phosphor bronze	AWG#18-22	TIN Plated	X5080H
PART NO	Material	Wire Range	Finish	Suitable XKB Housing

广东星坤科技股份有限公司

生效	日期
文件工程章	



DSND	SCALE: N/A	MODEL TYPE:
DWN	VIEW:	5.08mm Crimp Style Connectors
CHKD	UNIT: mm/in	PART NO.: X5080T-PSN
APPD	SIZE: A4	DWG NO.: X-X5080T-PSN
REVISIONS		WEIGHT
UNSPECIFIED TOLERANCES		SHEET
XKB INDUSTRIAL PRECISION CO., LIMITED		REVISION
		1/1
		A0