




Recommended P . C . B
Layout(±0.05)



Technical Date

Pin(outer sleeve):Brass,machined CuZn38pb2

Clp (Contact 6 Finger):Beryllium copper,heat teated

Insulator:PPS UL94V-0 colour:black

Current rating:3Amps

Mating PinØ:0.635/0.889mm

Forces:(polished steel gaugeØ0.66mm)

-Insertion:1.2N typ

-Withdrawal:0.6N typ

Mechanical Life:min 500 cycles

Contact resistance: 10mΩ max

Dielectric strength:1000V

Operating temperature:-40 °C to +105°C

Soldering temperature:+255°C

X5521 F V -2xXX- C85 D30 - 1150
① ② ③ ④ ⑤ ⑥ ⑦

1.Series No

2.Category:F-Female

3.Welding Board Angle:V-Straight 180°


4.Row No-Pin No:2xXX-2x01Pin-2xXXPin

5.Plastic Height:C=8.5mm

6.Pin Length:D=3.0mm

7.1150:Type1150

X5521FV-2xXX-C85D30-1150	PPS	Brass	X5521W
PART NO	Material	Material(Pin)	Suitable XKB Wafer
DSND		SCALE: N/A	MODEL TYPE: 2.54mm BTB Style Connector
DWN		VIEW:	PART NO.: X5521FV-2xXX-C85D30-1150
CHKD		UNIT: mm/in	DWG NO.: X-X5521FV-2xXX-C85D30-1150
APPD		SIZE: A4	
XKB INDUSTRIAL PRECISION CO.,LIMITED			WEIGHT
			SHEET
			REVISION
			1/1
			A0



ΔX
ΔX
ΔX
MARK

DESCRIPTION

DATE

REVISED

APPROVED

REVISIONS

UNSPECIFIED TOLERANCES

www.helloxkb.com www.helloxkb.cn www.xk-dg.cn

XKB

文件工程章