

## 备用钳口 - CF 500/DIE RCI 6-1 - 1212691


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



用于压接的机械 CF 500, 适用预绝缘电缆端头 (C ... RCI... and C ... FCI...) 0.5 ... 6 mm<sup>2</sup>



### 关键商业数据

包装单位	1 STK
GTIN	 4 046356 714563
GTIN	4046356714563
Sales Key	BG323Z

### 技术数据

#### 尺寸

电缆直径	0.9 mm ... 2.9 mm
------	-------------------

#### 概述

压缩	非对称压接
最小横截面	0.5 mm <sup>2</sup>
最大横截面	6 mm <sup>2</sup>
最小横截面	0.5 mm <sup>2</sup>
最大横截面	6 mm <sup>2</sup>

### 认证

认证

认证

EAC

## 备用钳口 - CF 500/DIE RCI 6-1 - 1212691

认证

防爆认证

---

认证详情

EAC



RU C-  
DE.AI30.B.01549

附件

附件

盖板

端板 - CF 500/COV RCI - 1212255



压接机 CF 500 保护盖，适用于绝缘电缆端头 0.14 - 6 mm<sup>2</sup> (RCI 1.5/6) 和车削插针 0.14 - 4 mm<sup>2</sup> (TC 4)