



PCB LAYOUT

- SPECIFICATIONS**
- 1、Current Rating: 7A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000MΩ Min
 - 6、Withstanding Voltage: 1500V AC/minute
 - 7、Material: Wafer Nylon66, UL94V-0
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A5801-02AW	5.08	10.16
A5801-03AW	10.16	15.24
A5801-04AW	15.24	20.32
A5801-05AW	20.32	25.40
A5801-06AW	25.40	30.48
A5801-07AW	30.48	35.56
A5801-08AW	35.56	40.64
A5801-09AW	40.64	45.72
A5801-10AW	45.72	50.80
A5801-11AW	50.80	55.88
A5801-12AW	55.88	60.96
A5801-20AW	96.52	101.60

	单位	mm
	比例	SCALE
x.±0.5	x.±	
.x±0.30	.x.±	
.xx±0.20	.xx.±	
.xxx±0.005, xxx.±	.xxx.±	

泰华电子有限公司
TaiHua Electronics Co., Ltd

标准:	版本:	A0	产品名称	5.08平弯 WAFER DIP TYPE
APPROVED BY	页次:	1/1	产品料号	TH-A5081-1AW
审核:	日期:		客户料号	
CHECKED BY	制图:	封文雅	客户料号	
日期:	日期:	2022.3.1	客户料号	
DRAWN BY	日期:		客户料号	