


PCB LAYOUT

- SPECIFICATIONS**
- 1、Current Rating: 2A AC, DC
  - 2、Voltage Rating: 250V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 1000MΩ Min
  - 6、Withstanding Voltage: 1000V AC/minute
  - 7、Material: Wafer Nylon66, UL94V-0  
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A2006-02AW	2.00	6.00
A2006-03AW	4.00	8.00
A2006-04AW	6.00	10.00
A2006-05AW	8.00	12.00
A2006-06AW	10.00	14.00
A2006-07AW	12.00	16.00
A2006-08AW	14.00	18.00
A2006-09AW	16.00	20.00
A2006-10AW	18.00	22.00
A2006-11AW	20.00	24.00
A2006-12AW	22.00	26.00
A2006-20AW	38.00	42.00



单位  
UNIT

mm

比例 SCALE	单位 UNIT	mm
X ± 0.5	X ±	
X ± 0.30	X ±	
.XX ± 0.20	.XX ±	
.XXX ± 0.005, XXX ±	.XXX ±	

核准: APPROVED BY	版本: A0	产品名称 Production name	HY弯针 WAFER DIP TYPE
审核: CHECKED BY	页次: 1/1	产品料号 Product No	TH-A2006-NAW
制图: DRAWN BY	日期: 2022.9.5	客户料号 Client No	

**泰华电子有限公司**  
**TaiHua Electronics Co., Ltd**

版本 REV	变更事项 CHANGE CONTENT	依据 REFERENCE	变更日期 DATE
A0			