


- SPECIFICATIONS**
- 1、Current Rating: 2A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000MΩ Min
 - 6、Withstanding Voltage: 800V AC/minute
 - 7、Material: Nylon66, UL94V-0

编 号	尺寸 (mm)	
	A	B
B2005-02Y	2.00	4.80
B2005-03Y	4.00	6.80
B2005-04Y	6.00	8.80
B2005-05Y	8.00	10.80
B2005-06Y	10.00	12.80
B2005-07Y	12.00	14.80
B2005-08Y	14.00	16.80
B2005-09Y	16.00	18.80
B2005-10Y	18.00	20.80
B2005-11Y	20.00	22.80
B2005-12Y	22.00	24.80
B2005-16Y	30.00	32.80

PCB LAYOUT



单位 UNIT	mm
比例 SCALE	1:1
公差: TOLERANCE	mm
APPROVED BY	.x±.x
CHECKED BY	.xx±.xx
制图: DRAWN BY	.xxx±0.005, .xxx±.xxx

泰华电子有限公司
TaiHua Electronics Co., Ltd

版本: VERSION	A0	产品名称 Product name	JC290FL座
页次: PAGE	1/1	产品料号 Product No	TH-B2005-NV
日期: DATE		客户料号 Client No	
		制图: DRAWN BY	封文彬 2022.3.5