



PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 300V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltage: 800V AC/minute
- 7、Material: Wafer Nylon6t, UL94V-0
PIN Brass Tin-plated
Solder tab Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A2021-1-02AB	2.00	8.00
A2021-1-03AB	4.00	10.00
A2021-1-04AB	6.00	12.00
A2021-1-05AB	8.00	14.00
A2021-1-06AB	10.00	16.00
A2021-1-07AB	12.00	18.00
A2021-1-08AB	14.00	20.00
A2021-1-09AB	16.00	22.00
A2021-1-10AB	18.00	24.00
A2021-1-11AB	20.00	26.00
A2021-1-12AB	22.00	28.00
A2021-1-15AB	28.00	34.00



单位	mm
比例	1:1

公差	X. ±0.5	X. ±0.5
公差	.X ±0.30	.X ±0.5
公差	.XX ±0.20	.XX ±0.5
公差	.XXX ±0.005	.XXX ±0.5

深圳市泰华电子有限公司
TaiHua Electronics Co., Ltd

核准:	版本:	产品名称	PEA立贴 WAFER SMT TYPE
APPROVED BY	A0	Production name	
审核:	页次:	产品编号	TH-A2021-02-NAB
CHECKED BY	1/1	Product No	
制图:	日期:	客户编号	
DRAWN BY	2022.9.5	Client No	
封文辉			