


PCB LAYOUT

- SPECIFICATIONS**
- 1、Current Rating: 3A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000MΩ Min
 - 6、Withstanding Voltage: 1000V AC/minute
 - 7、Material: Wafer Nylon66, UL94V-0
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A2501-02AW	2.50	7.50
A2501-03AW	5.00	10.00
A2501-04AW	7.50	12.50
A2501-05AW	10.00	15.00
A2501-06AW	12.50	17.50
A2501-07AW	15.00	20.00
A2501-08AW	17.50	22.50
A2501-09AW	20.00	25.00
A2501-10AW	22.50	27.50
A2501-11AW	25.00	30.00
A2501-12AW	27.50	32.50
A2501-20AW	47.50	52.50



单位 UNIT mm

比例 SCALE

X. ± 0.5 X* ±
 . X ± 0.30 X* ±
 . XX ± 0.20 . XX* ±
 . XXX ± 0.003 . XXX* ±

批准: APPROVED BY	版本: A0	产品名称: TJC3弯针 WAFER DIP TYPE
审核: CHECKED BY	页次: 1/1	产品料号: TH-A2501-2AW
制图: DRAWN BY	日期:	客户料号:

深圳市泰华电子有限公司
TaiHua Electronics Co., Ltd

版本: 1.00	客户料号: 0100000000	图号: TH-A2501-2AW	备注: 1.00
----------	------------------	------------------	----------