


PCB LAYOUT

编号	尺寸 (mm)		
	A	B	C
A3961-02AWB	3.96	9.90	11.88
A3961-03AWB	7.92	13.86	15.84
A3961-04AWB	11.88	17.82	19.80
A3961-05AWB	15.84	21.78	23.76
A3961-06AWB	19.80	25.74	27.72
A3961-07AWB	23.76	29.70	31.68
A3961-08AWB	27.72	33.66	35.64
A3961-09AWB	31.68	37.62	39.60
A3961-10AWB	35.64	41.58	43.56
A3961-11AWB	39.60	45.54	47.52
A3961-12AWB	43.56	49.50	51.48

SPECIFICATIONS

- 1、Current Rating: 7A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltage: 1500V AC/minute
- 7、Material: Wafer LCP, UL94V-0
PIN Brass Tin-plated



X. ±0.5	X*±
. X±0.30	. X*±
. XX±0.20	. XX*±
. XXX±0.008, XXX*±	

深圳市泰华电子有限公司
TaiHua Electronics Co., Ltd

单位 UNIT	mm
比例 SCALE	
核准: APPROVED BY	版本: A0
审核: CHECKED BY	图次: 1/1
制图: DRAWN BY	日期: 2022.10.24
	封文辉
	客户编号
	产品名称
	Production name
	产品料号
	Product No
	客户料号
	Client No
	日期:
	图次:
	核准:
	审核:
	比例:
	单位:

版本	客户名称	客户料号	客户日期
A0	TAIHUA ELECTRONICS	TH-A3961-NAWB	2022.10.24