


2~5A

- SPECIFICATIONS**
- 1、Current Rating: 3A AC, DC
  - 2、Voltage Rating: 250V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 1000MΩ Min
  - 6、Withstanding Voltage: 1000V AC/minute
  - 7、Material: Wafer Nylon46, UL94V-0  
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A2508-02A	2.50	7.50
A2508-03A	5.00	10.00
A2508-04A	7.50	12.50
A2508-05A	10.00	15.00
A2508-06A	12.50	17.50
A2508-07A	15.00	20.00
A2508-08A	17.50	22.50
A2508-09A	20.00	25.00
A2508-10A	22.50	27.50
A2508-11A	25.00	30.00
A2508-12A	27.50	32.50
A2508-13A	30.00	35.00
A2508-14A	32.50	37.50
A2508-15A	35.00	40.00
A2508-20A	47.50	52.50

**PCB LAYOUT**



单位	mm
比例	
SCALE	
公差:	X.±0.5 X*±
APPROVED BY	.X±0.30 X*±
审核:	.XX±0.20 .XX*±
CHECKED BY	.XXX±0.008 .XXX*±
制图:	
DRAWN BY	

深圳市泰华电子有限公司  
**TaiHua Electronics Co., Ltd**

版本:	A0	产品名称	XA单排直针 WAFER DIP TYPE
审核:	1/1	产品料号	TH-A2508-NA
制图:	封文辉	客户料号	
DRAWN BY	2022.9.6	Client No	

版本	客户料号	客户料号	客户料号
1/1	TH-A2508-NA	TH-A2508-NA	TH-A2508-NA