



PCB LAYOUT

编 号	尺寸 (mm)	
	A	B
A1500-02A	1.50	4.50
A1500-03A	3.00	6.00
A1500-04A	4.50	7.50
A1500-05A	6.00	9.00
A1500-06A	7.50	10.50
A1500-07A	9.00	12.00
A1500-08A	10.50	13.50
A1500-09A	12.00	15.00
A1500-10A	13.50	16.50
A1500-11A	15.00	18.00
A1500-12A	16.50	19.50
A1500-16A	22.50	25.50
A1500-20A	28.50	31.50

- SPECIFICATIONS
- 1、Current Rating: 1A AC, DC
 - 2、Voltage Rating: 100V AC, DC
 - 3、Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
 - 4、Contact Resistance: $20\text{m}\Omega$ Max
 - 5、Insulation Resistance: $500\text{M}\Omega$ Min
 - 6、Withstanding Voltage: 500V AC/minute
 - 7、Material: Wafer PBT/PA46 White/Beige, UL94V-0
PIN Brass Tin-plated



深圳市泰华电子有限公司
TaiHua Electronics Co., Ltd

单位	mm
比例	
核准:	版本: A0
APPROVED BY	Production name
审核:	ZH直钻 WAFER DIP TYPE
CHECKED BY	产品料号
制图:	Product No
DRAWN BY	客户料号
	日期:
	Client No

版本	客户料号	客户料号	客户料号
1.00	01500-000001	TH15000001	TH15000001