



REV.	ECN NO.	DATE	SIGN	DESCRIPTION
C	C201441	2020/09/17	Vicky	△C X2
D	C210219	2021/03/17	Vicky	△D X4
E	C210796	2021/05/24	Vicky	△E X1



Pin Out	Pin #	Wire	Color
5		Green	綠
4		Black	黑
3		Blue	藍
2		White	白
1		Brown	棕



△12-XXBMIM-SR8AXX
 XX: No. Of Pin
 XX: 01~99Meters
 01: 01Meter
 02: 02Meters
 :
 :
 99: 99Meters
 Cable Length(L): 01~99Meters

- △ Note:
- * RoHS Compliant
 - * @L Important dimension
 - * Waterproof rate: IPX8, mated 1m/24h
 - * Connector
 - △ Housing: Thermoplastic, Black
 - Pin: Copper alloy, Gold plated
 - Nut: Metal
 - Outer mold: Thermoplastic, Black
 - * Cable: UL2464, 22#*5C+Talcum, OD=5.5mm, PVC Jacket, UV Resistant, Black
 - △ * Cable length tolerance:
- | | |
|-------------------|------------|
| 1M: | +50/-0 mm |
| 1M < L ≤ 3M: | +100/-0 mm |
| 3M < L ≤ 5M: | +150/-0 mm |
| 5M < L ≤ 10M: | ±100 mm |
| 10M < L ≤ 20M: | ±200 mm |
| 20M < L ≤ 30M: | ±300 mm |
| △E 30M < L ≤ 99M: | ±500 mm |

Pin Assignments Front View

UNIT:mm	TITLE O SEN, M12 A (I) △△	
TOLERANCE ±0.5mm	CABLE W/O SR, M, I, MOLDING	
SCALE Free	SHEET 1	OF 1
REV. E	SIZE A4	@: Inspection Item

Amphenol LTW
 安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY Prune	DATE 2009/01/14
DWG. NO △12-XXBMIM-SR8AXX	CHECKED BY Tina	DATE 2009/01/14
CUSTOMER ALTW	APPROVED BY Luke	DATE 2009/03/26

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.